

THIS MATERIAL SAFETY DATA SHEET CONFORMS TO THE REQUIREMENTS OF ANSI Z400.1.
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (OSHA HAZARD COMMUNICATION STANDARD).
IMPORTANT: READ THIS MSDS BEFORE HANDLING OR DISPOSING OF THIS PRODUCT.

SECTION I – PRODUCT & COMPANY IDENTIFICATION

MANUFACTURER / DISTRIBUTOR Hitachi America, Ltd
50 Prospect Avenue
Tarrytown, NY 10591

PRODUCT NAME JP-E78 Printing Ink

MATERIAL USES Industrial coding applications; Ink Jet Printers

PRODUCT CODE X (22, 45, 53) 0383

NON-EMERGENCY PHONE 914-524-6685

EMERGENCY PHONE CHEMTREC (800) 424-9300

SECTION II – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	CAS#	PERCENT RANGE (%)
Ethanol	64-17-5	40 - 70
Acetone	67-64-1	3 - 7
Propylene Glycol	57-55-6	1 - 5
Ammonium Hydroxide	1336-21-6	0.5 - 1.5
FD&C Red #3	16423-68-0	1 - 5

SECTION III - HAZARDS IDENTIFICATION

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS)

HEALTH	1	FLAMMABILITY	3	REACTIVITY	0	PERSONAL PROTECTION	B
--------	---	--------------	---	------------	---	---------------------	---

NOTICE: THESE RATINGS ARE FOR GENERAL RAPID INTERPRETATION. THE END-USER IS RESPONSIBLE FOR DETERMINING THE PROPER PROTECTIVE PROCEDURES.

EMERGENCY OVERVIEW

Warning! Flammable Liquid and Vapor. Skin, Eye and Mucous Membrane Irritant. Do not use near fire or flame. May be fatal or cause blindness if swallowed. Avoid contact with skin, eyes and mucous membranes. If skin contact occurs, wash skin with mild soap and water. If splashed in eyes, flush with water. If inhaled, remove to fresh air. In medical emergency contact Poison Control Center ([USA 800.222.1222](tel:8002221222)). Read MSDS before using.

EXPOSURE EFFECTS AND RELATED SYMPTOMS

ETHANOL	Nausea, vomiting, flushing, mental excitement or depression, drowsiness, impaired perception, uncoordination, stupor, coma and death may occur.
ACETONE	A skin and severe eye irritant. Experimental reproductive effects. Narcotic in high concentration.
PROPYLENE GLYCOL	Slightly toxic by ingestion. Eye and skin irritant.
AMMONIUM HYDROXIDE	Severe irritant to eyes & mucous membranes. Human poison by ingestion.
FD&C RED #3	Poison by intravenous route. Moderately toxic by ingestion.



F - Highly Flammable



Xi - Irritant

RISK STATEMENTS

R11	Highly Flammable
R36/37/38	Irritating to eyes, respiratory system and skin
R66	Repeated exposure may cause skin dryness or cracking
R67	Inhalation of vapors can provoke sleepiness and dizziness

SAFETY STATEMENTS

S2	Keep away from children.
S7	Keep container tightly closed
S16	Keep away from sources of ignition - No Smoking!
S25	Avoid contact with eyes
S36/37	Wear suitable protective clothing and gloves
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)

SECTION IV - FIRST AID MEASURES

ORAL INGESTION	Do not induce vomiting unless directed to do so by medical personnel. Seek immediate medical attention.
EYE CONTACT	Flush with water for 15 minutes and seek medical attention.
SKIN CONTACT	Wash with soap and water. Wash contaminated clothing before reuse. Seek immediate medical attention.
INHALATION	Remove to fresh air, if not breathing, give artificial respiration and seek medical attention.

SECTION V - FIREFIGHTING MEASURES

EXTINGUISHING MEDIA	Alcohol Resistant foam or dry chemical
HAZARDOUS COMBUSTION PRODUCTS	Carbon Monoxide, Carbon Dioxide
FIRE FIGHTING PROCEDURES	Wear self-contained breathing apparatus with full facepiece operated in the positive pressure demand mode.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Keep away all sources of ignition from spill. If spill is indoors, ventilate areas of spill and soak up the spill with absorbent material. Do not let spilled or leaking material enter watercourse.

SECTION VII - HANDLING AND STORAGE

HANDLING	Avoid contact with eyes. Wash hands thoroughly with soap and water after handling. Utilize proper grounding with containers of material.
STORAGE	Protect from freezing. Overheating may cause container to rupture. Covered storage in a cool, dry place out of direct sunlight is preferable. Keep container tightly sealed until ready for use. Store away from ignition sources.

SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION	If workplace exposure limit(s) of product or any other component is exceeded, a NIOSH/OSHA approved respirator is advised. (See your safety equipment supplier for specific details.)
VENTILATION	Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/ TLV.
PROTECTIVE GLOVES	Wear chemical resistant gloves. (Consult your safety equipment supplier.)
EYE PROTECTION	Wear chemical splash goggles in compliance with OSHA regulations. However, OSHA regulations also permit other types of safety glasses.
OTHER PROTECTIVE EQUIPMENT	Wear impervious clothing and boots to prevent prolonged exposure.

OCCUPATIONAL EXPOSURE LIMITS:

INGREDIENT	ACGIH TLV*	OSHA PEL*
Ethanol	1000	1000
Acetone	750	750
Propylene Glycol	Not Established	Not Established
Ammonium Hydroxide	35	35
FD&C Red #3	Not Established	Not Established

SECTION IX - PHYSICAL & CHEMICAL PROPERTIES

PHYSICAL STATE	Liquid
COLOR	Red
ODOR	Solvent odor
BOILING RANGE	~ 78° C
MELTING RANGE	~ - 130° C
SPECIFIC GRAVITY (WATER=1)	0.849
DENSITY (lbs / gal)	7.08
EVAPORATION RATE (N-BUTYL ACETATE=1)	~ 1.9
PERCENT VOLATILE BY VOLUME (%)	77.5%
VAPOR PRESSURE	~ 44 mm of Hg @ 20° C
VAPOR DENSITY (AIR=1)	Greater than air
FLASH POINT (TCC)	21° C
AUTO IGNITION TEMPERATURE	~ 422° C
UPPER FLAMMABLE LIMIT (%By Vol.)	19
LOWER FLAMMABLE LIMIT (%By Vol.)	3.3
SOLUBILITY IN WATER	Miscible
SOLUBILITY IN ORGANIC SOLVENTS	Miscible
pH	Not Applicable

SECTION X - STABILITY & REACTIVITY

CONDITION OF INSTABILITY	None Known
CONDITIONS OF REACTIVITY	Not applicable
INCOMPATIBILITY	Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS	Carbon Monoxide, Carbon Dioxide
EXPLOSION DATA (SENSITIVE TO MECHANICAL IMPACT)	No
EXPLOSION DATA (SENSITIVE TO STATIC DISCHARGE)	Yes

SECTION XI - TOXICOLOGICAL INFORMATION

INGREDIENT	TOXICOLOGICAL INFORMATION **
Ethanol	LD ₅₀ Oral (rat) - 7060 mg / kg LC ₅₀ Inhalation (rat) - 20,000 ppm / 10 hr LD ₅₀ Intraperitoneal (rat) - 3750 mg / kg LD ₅₀ Intravenous (rat) - 1440 mg / kg LD _{Lo} Oral (dog) - 5500 mg / kg LD _{Lo} Subcutaneous (dog) - 6000 mg / kg
Acetone	LD ₅₀ Intravenous (rat) 5500 mg / kg LD ₅₀ Oral (rat) - 5800 mg / kg LC ₅₀ Inhalation (rat) - 50,000 mg / m ³ / 8 hr LD _{Lo} Oral (dog) - 8 g / kg LD ₅₀ Oral (rabbit) - 5340 mg / kg LD ₅₀ Skin (rabbit) - 20 g / kg
Propylene Glycol	LD ₅₀ Oral (rat) - 20 g / kg LD ₅₀ Intraperitoneal (rat) - 6660 mg / kg LD ₅₀ Subcutaneous (rat) - 22,500 mg / kg LD ₅₀ Intravenous (rat) - 6423 mg / kg LD ₅₀ Intramuscular (rat) - 14 g / kg
Ammonium Hydroxide	LD ₅₀ Oral (rat) - 350 mg / kg LD _{Lo} Oral (cat) - 750 mg / kg LD _{Lo} Intravenous (rabbit) - 10 mg / kg
FD&C Red #3	LD ₅₀ Oral (rat) - 1840 mg / kg LD ₅₀ Intravenous (rat) - 200 mg / kg LD ₅₀ Oral (mouse) - 1264 mg / kg LD ₅₀ Intravenous (mouse) - 370 mg / kg

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY	Not Available
PERSISTANCE / DEGRADABILITY	Not Available
HEAVY METALS	Concentration of lead, mercury, cadmium and hexavalent chromium [Cr(VI)] < 100 ppm No other ecological information is available for this product.

SECTION XIII - DISPOSAL CONSIDERATIONS

Absorb in vermiculite, floor absorbent or other non-combustible absorbent material and dispose in licensed facility. Observe all federal, state and local regulations.

SECTION XIV - TRANSPORT INFORMATION

DOT / TDG UN NUMBER & PROPER SHIPPING NAME	UN1210 PRINTING INK
DOT / TDG HAZARD CLASS	3
DOT / TDG LABEL	FLAMMABLE LIQUID
PACKING GROUP	II
EMERGENCY RESPONSE GUIDEBOOK NUMBER	129

SECTION XV - REGULATORY INFORMATION

TSCA	All chemicals used are listed on the TSCA Inventory.
CERCLA	The following product(s) is (are) listed by CERCLA: Acetone (3 - 7%) Ammonium Hydroxide (0.5 - 1.5%)
SARA 313	The following product(s) is (are) listed on SARA 313: Ammonium Hydroxide (0.5 - 1.5%)
California Prop 65	This product contains the following ingredients that the State of California has found to cause cancer, birth defects, or other reproductive harm, which requires a warning under the statute: none
International Regulations	The components of this product are listed on the chemical inventories of the following countries: Australia, Canada, Europe (EINECS), Japan, Korea, United Kingdom

SECTION XVI - OTHER INFORMATION

ISSUE DATE	March 2007
REVISION NUMBER	1
SUPERCEDES	n/a
PREPARED BY	Chris Jordan, Product Specialist

DISCLAIMER

Every effort has been made to ensure that the information in this MSDS is accurate and as complete as reasonably possible and of course all data herein are given in good faith. However, all information is furnished without warranty of any kind, and Hitachi America, Ltd. expressly negates any warranty of accuracy, expressed or implied; and Hitachi America, Ltd. assumes no responsibility for personal injury or damage to property to customers, vendors, or third parties if any information herein proves to be incorrect in any respect. Purchasers are encouraged to make independent determination of suitability and completeness of information from all sources to assure proper use and compatibility of product.

*NIOSH Publication #94-116

**Sax's Dangerous Properties of Industrial Mts. 11th Ed.