

# HITACHI

Inspire the Next

# CP-X327W



- 1,800 ANSI lumens
- Native XGA resolution
- 6 lbs.
- 16:9 mode
- Contrast ratio 350:1
- 2 RGB inputs/RGB output
- Component/composite/S-Video input
- Reverse image function for ceiling mount
- Vertical & horizontal keystone correction
- "My screen" (user programmable start-up screen)
- HDTV theater ready
- Remote control with mouse function
- Whisper mode 33dB
- Comes with soft case
- Color correction
- Kensington security slot
- Wide-angle lens
- FCC Class B
- Digital Zoom (x4)
- Picture freeze function
- Manual zoom & manual focus

## SPECIFICATIONS

<b>Model name</b>		CP-X327W	
Liquid crystal panel structure		0.7" polysilicon active-matrix TFT x 3	
Number of pixels		786,432 pixels (H 1,024 x V 768)	
Resolution		1,024 x 768 color pixels	
Colors		16.7 million colors	
Aspect ratio		Native 4:3/16:9 compatible	
Lens		Manual zoom 1:1.2 (F1.7 - 1.9), manual focus	
Throw ratio (distance:width)		1.49 ~ 1.79 : 1	
Lamp		150W UHB (130W in whisper mode)	
Brightness		1,800 ANSI lumens (1,440 ANSI lumens in whisper mode)	
Expected lamp life		Approx. 2,000 hours	
Contrast ratio		350 : 1	
Speakers		1W x 1	
Power supply		AC100-120V/AC220-240V 50/60Hz	
Power consumption		240W	
Operating temperature		32°F ~ 95°F	
Input signals		RGB	VGA, SVGA, XGA, SXGA/LXGA (COMPRESSED), MAC13", MAC16"
		Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60
		Component video	480i, 575i, 480p, 1,080i, 720p
Acoustic noise level		38dB (33dB in whisper mode)	
H sync		15kHz ~ 91kHz	
V sync		50Hz ~ 120Hz	
Vertical keystone correction		Digital keystone +/- 15°	
Horizontal keystone correction		Digital keystone +/- 5°	
Approvals		UL, C-UL, FCC Class B	
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 2
	RGB output	RGB	15-pin D-sub connector x 1
	Video input	S-video	Mini DIN 4-pin connector x 1
		Composite video	RCA jack x 1
		Component video	RCA jack x 3
	Audio		RCA jack x 2 (L/R)
	Control terminals		15-pin D-sub connector x 1 USB connector (USB mouse) x 1
	Compatible controls		PS/2, ADB, Serial, RS-232C (serial)
Chassis	Dimensions	11.6" x 3.0" x 9.1" (W x H x D)	
	Weight	6 lbs.	
	Supplied accessories	Remote control with mouse function, batteries (AA), RGB cable, RCA video/audio cable, USB cable, power cord, operator/safety manual, soft case	
Replace-ment parts	Lamp	CPX327LAMP (Part #: DT00521)	
	Remote control	(Part #: HLO1891)	



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	47	55
60	48	71	87
80	64	95	114
100	80	118	142
120	96	142	173
150	120	181	217
200	160	240	287

Throw ratio: 1.49-1.79:1 (distance:width)

\*: Measured in inches

### CP-S317/CP-X327 Dimensions (incl.protruding part)

