



- 1,400 ANSI lumens
- Native SVGA resolution
- 5 lbs
- RGB/component/composite/S-video inputs
- HDTV theater ready
- Short throw lens
- Manual zoom & manual focus
- Color temperature and gamma correction
- Reverse image function for ceiling mount
- Kensington security slot
- Vertical keystone correction
- Slide lens cover
- 16:9 mode
- Digital zoom & freeze function
- Comes with soft case
- Whisper mode 32dB

SPECIFICATIONS

Model name	CP-S225WA		
Liquid crystal panel structure	0.7" polysilicon active-matrix TFT x 3		
Number of pixels	480,000 pixels (H800 x V600)		
Resolution	800 x 600 color pixels		
Colors	16.7 million colors		
Aspect ratio	Native 4:3/16:9 compatible		
Lens	Manual zoom 1:1.2 (F2.0 - 2.3)		
Throw ratio (distance:width)	1.2 ~ 1.45 : 1		
Lamp	150W UHB		
Brightness	1,400 ANSI lumens (approx. 1,120 in whisper mode)		
Expected lamp life	Approx. 2,000 hours		
Contrast ratio	500 : 1		
Speakers	1W x 1		
Power supply	AC90-132V/AC220-240V 50/60Hz		
Power consumption	240W		
Operating temperature	0 ~ 35°C (32° ~ 95°F)		
Input signals	RGB	VGA, SVGA, XGA/SXGA/UXGA (COMPRESSED), MAC13", MAC16"	
	Composite video	NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM, PAL60, S-video	
	Component video	480i, 625i, 480p, 1,080i, 720p	
Acoustic noise level	36dB (32dB in whisper mode)		
H sync	15kHz ~ 91kHz		
V sync	50Hz ~ 120Hz		
Vertical keystone correction	Digital keystone +/- 10°		
Horizontal keystone correction	-		
Approvals	UL, C-UL, FCC Class B, CE, TUV		
Input/Output terminals	RGB input	RGB	D-sub 15-pin connector x 1
		Audio	Stereo mini jack x 1
	Video input	S-video	Mini DIN 4-pin input connector x 1
	Composite video		RCA jack x 1
	Component video		RCA jack x 3
	Audio		RCA jack x 2 (L/R)
Control terminals	Compatible controls		D-sub 15-pin connector x 1
			RS-232C (Serial)
Chassis	Dimensions		10.9" x 2.4" x 8.3" (W x H x D)
	Weight		5 lbs.
	Supplied accessories		Remote control, batteries (AA), power cord, RGB cable, RCA video/audio cable, multiple language operator/safety manual, handle strip and soft case.
Replacement parts	Lamp		CPS225LAMP (Part #: DT00401)
	Remote control		(Part #: HL01892) Mouse kit (Part #: RMU101) Optional



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	37	46
60	48	57	69
80	64	77	93
100	80	98	116
120	96	116	139
150	120	145	174
200	160	194	233

Throw ratio: 1.2 ~ 1.45:1 (distance:width)

*: Measured in inches

CP-S225/CP-X275 Dimensions

(incl. protruding part)

