

HITACHI

Inspire the Next

CP-S317W



- 1,700 ANSI lumens
- Native SVGA resolution
- 6 lbs
- 2 RGB inputs and RGB output
- Component/composite/S-video inputs
- HDTV theater ready
- FCC Class B
- 16:9 mode
- Vertical & horizontal keystone correction
- "My screen" (user programmable start-up screen)
- Reverse image function for ceiling mount
- Remote control with mouse function
- Color correction
- Whisper mode 33dB
- Supplied soft case
- Digital zoom (x4)
- Freeze function
- Manual zoom & manual focus
- Kensington security slot
- Wide-angle lens

SPECIFICATIONS

Model name		CP-S317W						
Liquid crystal panel structure		0.7" polysilicon active-matrix TFT x 3						
Number of pixels		480,000 pixels						
Resolution		800 x 600 color pixels						
Colors		16.7 million colors						
Aspect ratio		Native 4:3/16:9 compatible						
Lens		F1.7 - 1.9 manual zoom 1:1.2 manual focus						
Throw ratio (distance:width)		1.49 ~ 1.79 : 1						
Lamp		150W UHB (130W in whisper mode)						
Brightness		1,700 ANSI lumens (1,360 ANSI lumens in whisper mode)						
Expected lamp life		Approx. 2,000 hours (Approx. 4,000 hours in whisper mode)						
Contrast ratio		400 : 1						
Speakers		1W x 1						
Power supply		AC100-120V/AC220-240V 50/60Hz						
Power consumption		240W						
Operating temperature		32°F ~ 95°F						
Input signals		<table border="0"> <tr> <td>RGB</td> <td>VGA, SVGA, XGA, SXGA/UXGA (COMPRESSED), MAC13", MAC16"</td> </tr> <tr> <td>Composite video</td> <td>NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60</td> </tr> <tr> <td>Component video</td> <td>480i, 575i, 480p, 1,080i, 720p</td> </tr> </table>	RGB	VGA, SVGA, XGA, SXGA/UXGA (COMPRESSED), MAC13", MAC16"	Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60	Component video	480i, 575i, 480p, 1,080i, 720p
RGB	VGA, SVGA, XGA, SXGA/UXGA (COMPRESSED), MAC13", MAC16"							
Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60							
Component video	480i, 575i, 480p, 1,080i, 720p							
Acoustic noise level		38dB (33dB in whisper mode)						
H sync		15kHz ~ 91kHz						
V sync		50Hz ~ 120Hz						
Vertical keystone correction		Digital keystone +/- 15°						
Horizontal keystone correction		Digital keystone +/- 5°						
Approvals		UL, C-UL, FCC Class B						
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 2					
	RGB output	RGB	15-pin D-sub connector x 1					
	Video input	S-video	Mini DIN 4-pin connector x 1					
		Composite video	RCA jack x 1					
		Component video	RCA jack x 3					
	Audio		RCA jack x 2 (L/R)					
Control terminals		15-pin D-sub connector x 1 USB connector (USB mouse) x 1						
Compatible controls		PS/2, ADB, Serial, RS-232C (serial)						
Chassis	Dimensions		11.6" x 3.0" x 9.1" (W x H x D)					
	Weight		6 lbs.					
	Supplied accessories		Remote control with mouse function, batteries (AA), RGB cable, RCA video/audio cable, USB cable, power cord, operator/safety manual, soft case					
Replacement parts	Lamp		CP5317LAMP (Part #: DT00511)					
	Remote control		(Part #: HL01891)					



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	47	55
60	48	71	87
80	64	95	114
100	80	118	142
120	96	142	173
150	120	181	217
200	160	240	287

Throw ratio: 1.49 ~ 1.79:1 (distance:width)

*: Measured in inches

CP-S317/CP-X327 Dimensions (incl.protruding part)

