

| Screen Size 4.3 | | Throw distance | |
|-----------------|--------|----------------|------|
| Diagonal* | Width* | Min* | Max* |
| 30 | 24 | 34 | 41 |
| 60 | 48 | 70 | 84 |
| 80 | 64 | 93 | 112 |
| 100 | 80 | 117 | 140 |
| 120 | 96 | 140 | 169 |
| 150 | 120 | 176 | 211 |
| 200 | 160 | 234 | 282 |
| 300 | 240 | 352 | 423 |

Throw ratio: 1.5 - 1.7:1 (distance:width)
*Measured in inches



- 2,500 ANSI Lumens
- Native XGA Resolution
- 7.2 lbs
- 2 RGB inputs and 1 RGB Output
- Component / Composite / S-Video Inputs
- PC less presentation
- Transition Detector
- Digital Gamma Correction
- Auto Vertical Keystone Correction
- Remote Control with "My Buttons"
- 802.11 b/g Connect & Present with 4pc's wirelessly
- 34 dB (Whisper Mode)
- Supplied Soft Case
- My Screen / My Memory
- Whiteboard Mode
- Blackboard Mode
- Approx. 3,000 hrs (Whisper Mode)
- Security Bar
- Kensington Security Slot
- RJ-45 Port
- Audio Input / Output
- Input Source Naming
- Network Control, Maintenance & Scheduling
- USB 2.0 & SD removable memory reader

SPECIFICATIONS

| Model name | | CP-X268A series | |
|--------------------------------|----------------------|---|---|
| Liquid crystal panel structure | | 0.63" polysilicon active-matrix TFT x 3 | |
| Number of pixels | | 786,432 pixels | |
| Resolution | Video | 540 TV lines | |
| | RGB | 1024 dots X 768 lines | |
| Colors | | 16.7 million colors | |
| Aspect ratio | | Native 4:3/16:9 compatible | |
| Lens | | F1.7 - 1.9 manual zoom 1:1.2 | |
| Throw ratio (distance:width) | | 1.5 - 1.7:1 | |
| Lamp | | 200W UHB | |
| Brightness | | 2,500 ANSI lumens | |
| Expected lamp life | | Approx. 3,000 hrs (Whisper Mode) Approx. 2,000 hrs (Natural Mode) | |
| Contrast ratio | | 500 : 1 | |
| Speakers | | 1W x 1 | |
| Power supply | | AC100-120V/AC220-240V 50/60Hz | |
| Power consumption | | 330W | |
| Operating temperature | | 5°C ~ 35°C (41°F ~ 95°F) | |
| Input signals | RGB | VGA, SVGA, XGA, SXGA, SXGA+, UXGA, Mac13", MAC16" | |
| | Composite video | NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N | |
| | Component video | 480i, 576i, 480p, 720p, 1080i | |
| Acoustic noise level | | 39dB (34dB in whisper mode) | |
| H sync | | 15kHz ~ 106kHz | |
| V sync | | 50Hz ~ 120Hz | |
| Vertical keystone correction | | Digital keystone +/- 30° | |
| Approvals | | UL60950 / C-UL, FCC Part15, Class B, CE, EN60950 | |
| Input/Output terminals | RGB input | Analog RGB | 15-pin D-sub connector x 2 |
| | RGB output | RGB | 15-pin D-sub connector x 1 |
| | Video input | S-video | Mini DIN 4-pin connector x 1 |
| | | Composite video | RCA jack x 1 |
| | | Component video | RCA jack x 3 |
| | Audio | Input | Stereo mini jack x 2, RCA jack (L/R) x 1 |
| | | Output | Stereo mini jack x 1 |
| Others | | SD Card, USB 2.0 Memory (jpeg, bmp, png, MPEG4) | |
| Control terminals | | 9-pin D-sub connector x 1 (RS-232 control) USB connector (USB mouse) x 1 | |
| Chassis | Wireless | | 802.11 b/g |
| | Ethernet | | RJ-45 Port / 100BASE-T |
| | Dimensions | | 12.0" x 4.2" x 9.8" (W x H x D) |
| | Weight | | 7.2 lbs. |
| Replacement parts | Supplied accessories | | Remote Control, Batteries (AA), RGB Cable, RCA Video Cable, Power Cord, Multiple Language Operator / Safety Manual, Soft Case, Security Label, SD Wireless Card |
| | Lamp | | CPX260LAMP |
| | Remote control | | HL02221 |
| | Filter | | NJ22222 |



www.hitachi.us/digitalmedia